

Website: http://www.ideacamera.com Email:cctv@ideacamera.com
Global Sources Homepage Address: http://www.globalsources.com/ideacamera.co

1.3MP HD Vehicle Infrared Panoramic Camera, 3MP 1.39mm Panoramic Lens, 360°Vertical View, 180°Horizontal View, IP66 Outdoor Use, All Metal Housing, Top Good Quality.







Model Number: VR-VAHD360K-1.3MP

Main Features:

Black All Metal Housing
12pcs & 5 IR LEDs(15M IR Distance).
3MP 1.39mm HD Panoramic Lens.
BNC Interface Video Cable (OSD Menu optional).

Key specifications:

Image sensor (AR 0130+2433H DSP)



Website: http://www.ideacamera.com Email:cctv@ideacamera.com Global Sources Homepage Address: http://www.globalsources.com/ideacamera.co

Output AHD/TVI/CVI/CVBS, Effective resolution is 1280*960p.

OSD menu supports 12 different languages.

Strong light inhibition/privacy protection.

BLC/DPC, 2D noise reduction function.

OSD function (mirror image, color/ white-black, PAL/NTSC).

UTC Function (Working by Hybrid DVRs).

AGC type, day-night effect is distinct, various day-night modes can be switched by OSD menu With D-WDR.

Support UTC, 4-in-1, switched by OSD, Enhancement adjustment supported by OSD.

Power (600W) & Video (2KV) dual-lightning protection design, OSP antioxidant PCB, size 32*38 Dual-border.

Production Advantages:

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Efficiently working with almost HD Hybrid DVRs.

Lower price.

6-8 working day per order.

Production applications:

This is the best product of safety field. It and hard disk video recorders, cable, power supply, display, etc. Constitute a complete security system. Tts application is more extensive. Such as homes, factories, highways, office building, garden, community, or a large public places, etc.

Specifications:

Descriptions	1.3MP HD AHD Camera Module
Sensor	1/3 inch AR0130 CMOS+NVP2433 sensor
Video Resolution	1280(H)*960(V)
Signal system	PAL/NTSC(Switch by OSD Menu)
Minimum Illumination	color: 0.01Lux@ (F1.2, AGC ON), 0Lux with IR
	Black & White: 0.001Lux@ (F1.2, AGC ON), 0Lux with IR
S/N Ratio	≥41dB
BLC	AUTO



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: http://www.ideacamera.com
Email:cctv@ideacamera.com

Global Sources Homepage Address: http://www.globalsources.com/ideacamera.co

Shutter	1/50(1/60) seconds to 1/50,000 seconds
AWB	AUTO
IR Control Input Voltage	OFF(DC OV)/ ON:DC 3V-8V
Video Output	AHD/TVI/CVI/CVBS
OSD menu(12)	English/Simplified Chinese/Traditional
Video record occupation	1min≈24mb (4mm lens)
Working Voltage	DC 12V/42mA±6mA(wide voltage 9v-18v)
D/N Function	External(Default)/Auto/Color/White&Black (Switch by OSD Menu)
Synchronous Mode	inter-sync
Temperature and	- 20 °C~ 50 °C, humidity is less than 90% (no condensation)
Humidity	
Size	Standard 32*32 positioning hole, compatible with 38*38 hole
Accessories	AHD Camera Manual, warranty card/certification, 1 dryer