



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

**2MP H.265 IR Panoramic IP Camera with 5MP 1.44mm HD
Panoramic Lens, 360° Vertical View, 184° Horizontal View
Support Face Detection, VSS Mobile APP.**



Model: VR-VCAM360M-2MPV

Key features:

5MP 1.44mm HD Panoramic Lens.

Black all metal body.

Built-in 12pcs Strong IR LEDs.

Support 20 meters IR distance.

With high quality network video cable.



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Product characteristics:

2MP 1/2.9" CMOS Sensor (Sony323+Hi3516C V300).

Max video resolution: 1920*1080@25/30fps.

Support all channel face detection (upgrade IPC).

Support H.264/H.265/H.265+ Video compression.

360° Vertical View, 184° Horizontal View.

Support remote control by cellphone (VSS Mobile App).

Support computer client (IMS300).

Support ONVIF protocol (up to 2.6).

Support POE power supply (optional).

Standard 38*38 single board, Easy to install CCTV Camera.

Support IR-CUT (Day and night auto switch).

Support 1ch audio input, 1ch audio output, realize two-way phonetic dialogue.

Support 1ch alarm input.

Support 1 USB reserve interface.

Support 1ch CVBS output.

Support smart IR.

Support three bit stream.

Support 3D noise reduction and digital WDR.

Support private network penetration and cross browser access.

Product Advantages:

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Efficiently working with almost NVR.

Lower price.

6-8 working day per order.

Product applications:

This is the best product of safety field. It and hard disk video recorders、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Specifications:

2MP HD IP Module		
Model	VR-VCAM360M-2MPV	
System Structure	DSP	Embedded RTOS Design DSP(Hi3516C V300)
	Sensor	1/2.9" CMOS Sensor (SONY IMX323)
Video Code	Video Code Standard	H.265/ H.264 High Profile/Main Profile/ Base Line Profile/MJPEG
		H.265+/ H.264 High Profile+/Main Profile+/ Base Line Profile+
	Max Image Resolution	Main Stream: 1920*1080@25/30fps; Sub-stream1: 704*576@25/30fps; Sub-stream2: 1280*720@25/30fps;
	Stream Transmission	Three bit stream
	Video Code Rate	32Kbps~8MKbps
Image Adjustm ent	Low Illuminati on	Color 75B (AGC ON); Black&White 0.001Lux@F1.2 (AGC ON)
	Electronic Shutter	Auto (1/25~1/10000)
	D&N Transfor mation	Color/D&N/Photosensitive transformation/Mixed mode transformation
	White Balance	Auto/Locked white balance/Daylight lamp/Incandescent lamp/Florescent lamp/Manual
	Digital Noise Reduction	Support 2D/3D digital noise reduction
	WDR	Support digital WDR
	Video Adjustme nt	Sharpness/Brightness/Saturation/Contrast ratio/Chromaticity adjustable
	Image Mode	Transparent/Real



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

	Color Mode	Standard/Gorgeous
	Corridor Mode	Support
	Backlight Compensation	Support
	Penetrating Fog	Support
Interface	Signal Port	1 Photosensitive resistor, 1 IR-CUT Drive interface, Support Photosensitive resistor input signal and IR-CUT infrared linkage
	Smart IR Port	1
	Reset Port	1 Reset signal port
	Audio Port	1 Audio input, 1 Audio output
	Alarm Port	1 Alarm port
	Video Output	1 CVBS output port
	Power Port	1 DV12V power input port
	USB Port	1 Reserve port
	POE Port	1 POE Extensible port
	Network Lamp Port	1 Network lamp
	Network Port	1 个 RJ45 10/100M Network port
Function	Motion Detection	Support setting multiple detection area, Support setting multilevel sensitivity
	Capture Function	Support JPEG capture, Max image resolution of capturing
	Safety Characteristics	Support Password protection, Watermark function
	Character Superposition	Support Channel name/Date/Time superposition
		Support custom title superposition
		Support picture superposition
	Intelligent Alarm	Support network anomaly alarm, Occluding alarm



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

	Intelligent Function	Tripwire Testing
	Storage	Support FTP Storage
	Mobile Phone Client	Support Apple phone, Android phone monitoring
	Support Protocols	TCP/IP;UDP;HTTP;IGMP ;ICMP;DHCP;RTP/RTSP;DNS;DDNS;FTP ;NTP;PPPOE;UPNP;SMTP;SNMP
	Interface Protocols	Support ONVIF/CGI
Conventional Parameters	Power Supply	DC12V/POE (-P)
	Effect	Less than 1W (No IR Board)
	Lightning Protection	Power/Network/POE Comprehensive lightning protection, Accord with national standard GB/T17626.5, International standard IEC61000-4-5
	Size	38*38 (mm) Single board