



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

**5MP H.265 Metal IR Dome IP Camera with 5MP 3.6mm
Fixed Lens, 2592*1944P, Internal POE, Audio In, Support
Face Detection, ONVIF2.6, VSS Mobile App.**



Model: RC-DVF90E-5MPV-P-A

Key features:

5MP 3.6mm Fixed Lens (6,8mm Optional).

White metal body with strong bracket.

Built-in 32pcs IR LEDs.

Support 25 meters IR distance.

Internal POE, Audio In.

With high quality network video cable.

Main parameters:

32 bit DSP (1/1.8"SONY IMX178+3516A Sensor).

2592*1944@25/30fps High resolution.

Support Face Detection.

H.265/H.264 high profile.

Support Tri-Stream technology.

Support one channel audio input, one channel audio output.

Support two-way voice speaking.

Support one channel alarm input, one channel alarm output.



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Support one TF card interface, the maximum up to 128G.

Support one electric zoom interface.

Support one 485 interface.

Support one USB interface.

Support one CVBS output.

Support SMART IR.

Support 3D DNR, DWDR.

Support P2P and cross-browser access.

Mobile APP Name: VSS Mobile.

Computer client (IMS300).

Support ONVIF protocol (up to 2.6).

Product Advantages:

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Efficiently working with almost NVR.

Lower price.

6-8 working day per order.

Product applications:

This is the best product of safety field. It and hard disk video recorders、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.

Specifications:

5MP Standard Double-Boards IP Camera Module		
Product model	RC-DVF90E-5MPVP-P-A	
System Structure	DSP	Embedded RTOS, DSP(Hi3516A)
	Sensor	1/1.8" CMOS sensor (SONY IMX178)
Video Encoding	Video Encoding	H.265 Main Profile/MJPEG/ H.264HighProfile/ Main Profile/ BaseLine Profile
	Maximum Image Output	Main stream: 2592*1944@25/30fps; Auxiliary stream one and stream two can optional
	Auxiliary stream one	704*576/352*288



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

	Auxiliary stream two	1280*720/640*480/352*288
	Video Bite rate	32Kbps~8MKbps
Image Enhancement	Min. illumination	Color 0.01Lux/F1.2; black and white 0.001Lux/F1.2
	Electronic shutter	Auto (1/25 to 1/10000)
	Day/Night switch	Auto/color/B&W (Built-in IR_CUT)
	DNR	2D and 3D DNR
	WDR	Support DWDR
	Corridor pattern	support
	Video Adjust	Sharpness, Brightness, Saturation, Contrast Adjustable
Double-Board Interfaces	Signal interface	one photosensitive resistance signal interface, one IR_CUT drive interface support photo resistance signal links to IR-CUT and IR light
	Smart IR	One port
	Reset interface	One port
	Audio interface	One audio in; One audio out
	Power interface	One DC12V power input
	CVBS Interface	One Port
	DC-Iris Interface	One Port
	USB interface	One Port
	POE interface	One Extended Interface
	Network lamp interface	One Port
	Network interface	One RJ45 10/100M Port
	electric zoom interface	One Port
Function expansion board interfaces	Alarm interface	One alarm in; One alarm out
	485 interfaces	One port
	TF card interface	One port
Functions	Motion detection	Multiple detection zones, variable sensitivity levels
	Capture function	JPEG, capture resolution is the max coding resolution
	Security	Password protection and water marker
	OSD	Support Channel Name and Time
	Smart function	Perimeter Intrusion Detection
	Smart alarm	Network abnormal, cover alarm etc.
	Mobile client	VSSMOBILE for both iPhone and Android system phone
	Protocol support	TCP/IP; UDP; HTTP; IGMP ; ICMP; DHCP;



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

		RTP/RTSP; DNS; DDNS; FTP; NTP; PPPOE; UPNP; SMTP; SNMP
	Interface protocol	ONVIF/CGI
General	Power Supply	DC12V/POE(-P)
	Power Consumption	<2.5W (without infrared lamp board)
	Lightning Protection	Power, network, POE all lightning protection, meets with standard GB/T17626.5, and IEC61000-4-5
	Size	38*38 (mm) three Board