



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

8CH H.265 HD Professional NVR, Double antenna MIMO 802.11 b/g/n wireless networks, Max 8ch Playback, 4CH 1080P@20FPS or 8CH 720P@20FPS, VSS Mobile App.



Model: NVR-2208L-W/JN

Key features:

Video Output: 1* HDMI, 1* VGA
2*USB 2.0 interface
1* RS485 Interface

Key functions:

High performance chip (Hi3536D).
Support 8ch WIFI cameras.
Double antenna MIMO 802.11 b/g/n wireless networks.
4CH 1080P@20FPS or 8CH 720P@20FPS.
H.265/H.264 Profile.
Real time Playback (Max 8ch).
Bandwidth input: 32Mbps
Support ONVIF 2.6, Digital zoom, 3G Dongle supported.
Cloud storage (google drive/drop box), mobile alarm push.
Support Two-way voice intercom, UPNP, mobile phone surveillance.
Support Multi-Protocols, P2P, and Built-in free DDNS.
Support mobile APP (VSS Mobile).
Support computer client (IMS300).
Support 1 HDD (Up to 10TB)



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

With strong power (DC 12V 2A).

Offer services:

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Lower price.

6-8 working day per order.

Applications:

This is the best product of safety field. It and CCTV camera、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.

Parameters:

Model		NVR-2204L-W/JN	NVR-2208L-W/JN
OS		Embedded Linux	
Video&Audio input	IPC Input	4CH	8CH
	Incoming bandwidth	32Mbps	
	Outgoing bandwidth	32Mbps	
Video&Audio output	Audio Output	1CH,3.5mm output port	
	VGA	1CH,1920×1080,1280×1024,1280×720,1024×768	
	HDMI	1.4b 1920×1080,1280×1024,1280×720,1024×768	
Video&Audio decoding	IP channel Resolution	Main stream: up to 2560x1440 Auxiliary stream: D1	
	Video decoding	H.265 (Main Profile@Level 4.1) /H.264(Up to High Profile@Level 4.2)	
	Audio decoding	G.711A, G711U	
	Synchronous Playback	Up to 4CH	Up to 8CH
	Decoding Ability	4CH 1080P@20FPS	8CH 720P@20FPS or 4CH 1080P@20FPS
Other Function	Motion Detection	Zones: 396(22*18), Sensitivity: 1~6 (level 6 is highest)	
	Picture Capture	Support JPEG Capture	
HDD Interface	SATA	1 SATA Interface	
	Max Capacity	Unlimited	
External Interface	Network Interface	1 RJ45 10M/100M self-adaptive Ethernet interface	
	USB	2 USB2.0 Interfaces	
WIFI Function	WIFI Frequency	2.4GHz	
	Antenna	two external antenna	
	Bandwidth	300Mbps	
	WIFI Standard	IEEE802.11b/g/n	
Structure	Dimensions	410*293*60mm	
	Size	215*235*45mmmm	
	Weight	1Kg (without HDD)	
	Installation	Desktop Installation	
General	Power Supply	DC +12V 2A	
	Working Temperature	0℃--+45℃	
	Working Humidity	10%--90%	
	Consumption	7W(without HDD)	