SHENZHEN RISE ELECTRONIC CO., LTD.
Website: http://www.ideacamera.com Email:cctv@ideacamera.com
Global Sources Homepage Address: http://www.globalsources.com/ideacamera.co



2MP WIFI Outdoor Waterproof Solar Double Light Source PTZ Dome Camera, UBOX APP, Two-way Intercom, Cloud storage, Motion Detection.

Model: RC-HDG8210HSI3G2-TOA

Features:

The product can quickly sleep and wake up to achieve intelligent power saving.
High performance 1/2" black light full color image processor.
Solar charging with built-in batteries.
1080P HD video.
Ultra low power consumption and long standby.
Built-in microphone and speaker to support two-way voice intercom.
Support cloud storage for local storage.
The APP supports Android/ iOS.
Metal body, IP65 outdoor waterproof.

Notes:

Multi-version: Europe, the United States, China, Southeast Asia

Packing list:

1. Standard 1M USB cable * 1
2. Screw package * 1
3. Description * 1
4. Screwdriver *1
5. Hexagon wrench*1
6. Ball machine bracket*1

Size&weight:

Each packing: 290*200*170MM/

8pcs each box, packing size: 600*420*370MM

Weight: 1.84kg/pcs

Tech-parameter:

Product name	WiFi Solar Double Light Source PTZ Dome Camera	
Model	RC-HDG8210HSI3G2-TOA	
General	Main chip	HI3518E
	APP Operating System	Android, IOS
	Sensor	1/2″ Image Sensor PS5280LT
	Compressed format	H.264+/H.265
	Pixel	1920*1080 1080P
Networking way	WIFI	wifi
Alarm mode	Detection mode	PIR +Radar dual inductive detection
	Detection distance	0~12M
	Detection angle	100°
	Alarm mode	Dual induction confirms push alarm information to mobile phone
Cloud	Cloud angle	Level 355 ° Vertical 120°
	Rotate speed	Level 55°/s Vertical 40°/s
Night vision mode	Full color night vision	Illumination 0.00001LUX
	IR leds	IR LED Distance: 20M
	White-light sources	White light LED Distance: 20M
Sound	Built-in speaker	3W
	Built-in microphone	Monitoring scope :10M
Length	Focal length	3.6mm
	Angle	100°
Storage	Cloud storage	Cloud storage（Alarm recording）
	Local storage	TF card（Max 128G）
Power	Power mode	Solar enegy+18650 battery
	Solar cell power	7.8W
	Battery capacity	Max support 6 18650 battery （6*3000MA=18000MA）
	Max working power	4W
	Stand-by power	0.003W

Other	Working environment	Indoor/outdoor
	Working temperature	-30°~+60°
	Working Humidity	0%~90%RH