



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

78W 4Ports Standard 4+2 Full Gigabit PoE Switch, Internal Power.



Model: G0420GB

Key features:

Support 4*10/100/1000Mbps RJ45 ports;

Support 2*10/100/1000Mbps RJ45 uplink ports;

Whole powers≤78W, each port≤30W;

Transmit distance: ≤100M

Power Supply: 78W 52V 1.5A

1-4 ports support IEEE802.3af/at;

Supports 8K MAC address table depth;

Power priority mechanism, fast and forward, MAC automatic learning and aging;

IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode;

MOQ: 30pcs

Our services:

Offer 2-years product warranties.

Logistics convenient.

Support OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Lower price.



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

6-8 working day per order.

Advantages:

Occupied 4 POE power supply RJ45 port, all of 4 RJ45 ports are support IEEE802.3AF/AT standard power supply, each port max. Power reached 30W, whole power reached 78W, can be detected PD electric equipment who obey IEEE802.3AF/AT standard automatically.

Detailed parameters:

Model	G0420GB
Network standard	IEEE 802.3、IEEE 802.3u、IEEE 802.3ab、IEEE 802.3z、IEEE 802.1d、IEEE 802.1w、
	IEEE 802.1s 、IEEE 802.1Q、IEEE 802.1p、IEEE 802.3x、IEEE802.3af、IEEE802.3at
PoE port	4 10/100/1000Mbps RJ45 port
	2 10/100/1000Mbps RJ45 uplink port
PoE power supply	4 10/100/1000Mbps RJ45 port Support PoE+Power supply
	Whole power≤78W
	Each po≤30W
PoE connect	1-4 ports support IEEE802.3af/at
	Support 1/2+, 3/6- line pair
	End Bonding
Performance	Store and forward
	Supports 8K MAC address table depth
	16Gbps backplane bandwidth
Forwarding Rate	10BASE-T: 14880pps/port
	100BASE-TX: 148800pps/port
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging
	IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
Working Environment	Working temperature: -10℃~-55℃
Power supply	Each port ≤30W
	Whole≤78W
	DC 52V 1.5A
Size&weight	1 KG
	200mm×118mm×44mm(L×W×H)