

**2megapixels 1080p Wireless smart camera, E-Mail alarm, Motion detection, Manual recording, Alarm recording, With 2MP 3.6mm HD Fixed Lens, Support night vision, Support TF Card local storage (Max to 128G), Support remote control, PC client control.**

**Fob: US\$16.99~ US\$17.99**



**Model: RC-WPTD-2MP**

### **Product features:**

Wireless WIFI intelligent connection, Plug and Play, Easy to realize monitoring by mobile phone;  
1920\*1080P High definition image, dual antenna;  
3D audio processing technology, be sure high quality calling;  
Support local recording (Max 128G TF Card);  
Remote controlling by mobile phone, Omni bearing video monitoring;  
PC Management software (CMS, Simultaneously support 64ch devices);  
Support ONVIF Protocol, can connection to NVR (realizing recording more video);

### **Product applications:**

Widely used in various types of residential area (such as villas, communities etc.), small and medium-sized indoor spaces (small and medium-sized stores、small and medium-sized company office area etc.)

### **Product Advantages:**

Offer 2-years product warranties.  
Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Efficiently working with almost NVR.

Lower price.

6-8 working day per order.

## Product main parameters:

Model		RC-WPTD-2MP
Display	Image sensor	2MP CMOS
	Video resolution	1920×1080P
	Effective pixel	2megapixels
	Video compression standard	H.264/JPEG
	Video frequency	1 to 30fps
	Video bit rate	64Kbps ~ 8Mbps
	S/N	≥38dB
	Minimum illumination	Day mode(0.1Lux), 0.01 Lux (IR ON)
Lens	Interface size	M12
	Length collection	3.6mm
	Length viewing angle	90°
	Focus system	prime
Function	Privacy shelter	Each channels support 4 occlusion area block at the same time
	Exposure control	automation
	Gain control	automation
	White balance	automation
	Voice intercom	support
	D/N functionality	IR-CUT double filter switch , support colors turn to black.
	Video adjustment	Support contrast、luminance、saturation、acutance or picture image etc.
	Remote operation	System setting、stream management、storage management、user management、network management
	Mobile detection	support
	433 alert function	nonsupport ( optional )
	Detection alert	E-mail alert、client alert、FTP alert
	Local storage	Mat to 128G
Network	Ethernet	10/100M Ethernet
	Stream	Three stream
	Internet protocol	Standard HTTP.TCP/IP.ICMP.RTSP.RTP.UDP.RTCP.SMTP.FTP.DHCP.DNS.PPPOE

	Wireless network	Wi-Fi
	Internet transmission	Built-in cloud monitoring transmission protocol
<b>Hardware interface</b>	Audio input	Built-in 1 MIC
	Audio output	Built-in 1 speaker
	Reset	Restore the default settings
	Internet interface	1 RJ45
	Wireless interface	1 Wi-Fi extremal antenna interface
<b>PTZ</b>	Rotation	horizontal : 355°、 vertical : 120°
<b>Environment</b>	Temperature	-20°C ~ +50°C
	Humidity	10% ~ 90%
<b>Basic feature</b>	Infrared LEDs	11pcs LEDs
	Infrared distance	10 ~ 30 meters
	Power	DC 5V 2A
	Maximum powerful	≤3.65W
	Color/material	white /ABS plastic
	Size	100×135×128mm
	Weight	300g
	Installation	Bracket installation、 desktop installation、 lifting