SHENZHEN RISE ELECTRONIC CO., LTD.

Website: http://www.ideacamera.com Email:cctv@ideacamera.com
Global Sources Homepage Address: http://www.globalsources.com/ideacamera.co

2MP IR Waterproof Bullet Starlight AHD Camera with 5.0MP 3.6mm Starlight Lens, Star light (day and night all color),OSD Menu (optional), AHD/TVI/CVI/CVBS 4IN1 with UTC Control.

FOB: US$27.44/Per





Model Number: RC-BF75P-AHD-ST

Key specifications:

Image sensor: SONY291+NVP2441H
Effective pixels: 1920(H) x1080(V)
Video modes: AHD/TI/CVI/CVBS 4IN1
UTC Control: Supported
Starlight Functional: Day and night all time color
Electronic shutter: 1/50(1/60) seconds to 1/100,000 seconds
Video frame rate: 1920*1080 at 25fps, 1920*1080 at 30fps
Synchronization: internal
Photosensitive Resistance: 1 photosensitive resistance interface, support the photosensitive resistor input signal and image, IR-CUT, infrared lamp linkage
Minimum illumination: color：0. 01Lux@（F1.2，AGC ON），0Lux with IR.
Black & White：0.001Lux@（F1.2，AGC ON），0Lux with IR
S/N ratio: >52dB
Video output: 1Vp-p, 75Ω, BNC
Lens: 5.0megapixels 3.6mm Starlight Lens (6,8mm optional)
Day and night: automatic (ICR)

Backlight compensation: automatic
Gain control: automatic
White balance: automatic
Infrared: 42pcs IR LEDs
IR distance: 35meters
IR-cut: supported
Night vision: supported
Infrared spectrum: 850nm
Waterproof casing: IP66
Case Color: White
OSD MENU: Support 28 Languages (optional)

Product Advantages:

Offer 2-years product warranties.
Logistics convenient.
OEM/ODM.
CCC/CE/FCC Certified.
Strict product quality control.
Work with almost 5IN1 Hybrid DVR.
Lower price.
6-8 working day per order.

Product applications:

This is the best product of safety field. It and hard disk video recorders、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.

1080P HD Analog Video Camera Module

Descriptions	1080P HD Analog Video Camera Module
Sensor	SONY291+NVP2441H sensor
Video Modes	AHD/TVI/CVI/CVBS 4IN1
UTC Function	Supported
Video Resolution	PAL/NTSC : 1920*1080
Minimum Illumination	color：0. 01Lux@（F1.2，AGC ON），0Lux with IR
	Black & White：0.001Lux@（F1.2，AGC ON），0Lux

Photosensitive Resistance	1 photosensitive resistance interface, support the photosensitive resistor input signal and image, IR-
D/N(automation)	Day and Night all time color
IR CUR	Supported
Shutter	1/50(1/60) seconds to 1/100,000 seconds
Day and Night Function	Support IR-CUT
Lens Parameters	C/CS interface, M12 lens optional
Synchronous Mode	inter-sync
Noise-signal Ratio	>58dB
Temperature and Humidity	- 10 ℃~ 60 ℃, humidity is less than 90% (no condensation)
Power	DC12V±10%
Consumption	<5W
Size	Standard 38*38 positioning hole8