



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com
Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

2MP AHD HD Vehicle infrared conch Camera with Sony sensor, 3.0Megapixels 2.8mm HD Fixed Lens, Working with Mobile Car DVR.



Model Number: RC-VAHD-3C-2MP

Features:

3.0megapixels 2.8mm HD Fixed Lens (3.6, 4,6mm Optional).
Black plastic casing.
Built-in 15pcs IR LEDs
12meters IR distance.
With aviation plug video cable.
Waterproof IP66.

Key parameters:

Image sensor: SONY323+NVP2441H
Effective pixels: 1920(H) x1080(V)



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com
Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Electronic shutter: 1/50(1/60) seconds to 1/100,000 seconds

Video frame rate: 1920*1080 at 25fps, 1920*1080 at 30fps

Synchronization: internal

Photosensitive Resistance: 1 photosensitive resistance interface, support the photosensitive resistor input signal and image, IR-CUT, infrared lamp linkage

Minimum illumination: color: 0.01Lux@ (F1.2, AGC ON), 0Lux with IR.

Black & White: 0.001Lux@ (F1.2, AGC ON), 0Lux with IR

S/N ratio: >52dB

Video output: 1Vp-p, 75Ω, BNC

Backlight compensation: automatic

Gain control: automatic

White balance: automatic

Night vision: supported

Infrared spectrum: 850nm

Product Advantages:

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Work with almost Analog and AHD-DVR.

Lower price.

6-8 working day per order.

Program	1080P HD Analog Video Camera Module
Sensor	SONY323+NVP2441H sensor
Video Resolution	PAL/NTSC : 1920*1080
Minimum Illumination	color: 0.01Lux@ (F1.2, AGC ON) , 0Lux with IR Black & White: 0.001Lux@ (F1.2, AGC ON) , 0Lux with IR
Photosensitive Resistance	1 photosensitive resistance interface, support the photosensitive resistor input signal and image, IR-CUT, infrared lamp linkage
D/N(automation)	Supported
IR CUR	Supported
Shutter	1/50(1/60) seconds to 1/100,000 seconds
Day and Night Function	Supported



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Lens Parameters	C/CS interface, M12 lens optional
Synchronous Mode	inter-sync
Noise-signal Ratio	>58dB
Temperature and Humidity	- 10 °C~ 60 °C, humidity is less than 90% (no condensation)
Power	DC12V±10%
Consumption	<5W
Size	Standard 38*38 positioning hole8