



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

2MP IR Waterproof Bullet HD AHD Camera with OSD Menu, AHD/TVI/CVI/CVBS 4IN1, Support UTC Control.



Model Number: RC-BM75EAHD-3E

Main Features:

White casing with strong bracket
42pcs \varnothing 5 IR LEDs(35M IR Distance).
Metal+ glass strong lens.
2MP 2.8-12mm Varifocal Lens.
BNC Interface Video Cable (With OSD Menu).

Key specifications:

Image sensor (SOI F22+Fullhan V30E DSP)
Output AHD/TVI/CVI/CVBS, Effective resolution is up to 1920*1080/960H.
OSD menu supports 12 different languages.
Strong light inhibition/privacy protection.
BLC/DPC, 2D noise reduction function.
OSD function (mirror image, color/ white-black, PAL/NTSC).
UTC Function (Working by Hybrid DVRs).
AGC type, day-night effect is distinct, various day-night modes can be switched by OSD menu
With D-WDR.
Support UTC, 4-in-1, switched by OSD, Enhancement adjustment supported by OSD.



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Power (600W) & Video (2KV) dual-lightning protection design, OSP antioxidant PCB, size 32*38
Dual-border.

Production Advantages:

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Efficiently working with almost HD Hybrid DVRs.

Lower price.

6-8 working day per order.

Production applications:

This is the best product of safety field. It and hard disk video recorders、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.

1080P HD Analog Video Camera Module

Descriptions	2MP HD AHD Camera Module
Sensor	1/2.9 inch SOI F22+Fullhan V30E sensor
Video Resolution	1920(H)*1080(V)
Effective pixels	Approx.2.07M pixels
Signal system	PAL/NTSC(Switch by OSD Menu)
Minimum Illumination	color: 0.01Lux@ (F1.2, AGC ON) , 0Lux with IR Black & White: 0.001Lux@ (F1.2, AGC ON) , 0Lux with IR
S/N Ratio	≥41dB
BLC	AUTO
Shutter	1/50(1/60) seconds to 1/50,000 seconds
AWB	AUTO
IR Control Input Voltage	OFF(DC OV)/ ON:DC 3V-8V
Video Output	AHD/TVI/CVI/CVBS
OSD menu(12)	English/Simplified Chinese/Traditional Chinese/German/French/Italian/Spanish/Polish/Portuguese/Dutch/Turkish



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Video record occupation	1min \approx 24mb (4mm lens)
Working Voltage	DC 12V/76mA \pm 6mA(wide voltage 9v-18v)
D/N Function	External(Default)/Auto/Color/White&Black (Switch by OSD Menu)
Synchronous Mode	inter-sync
Temperature and Humidity	- 20 °C~ 50 °C, humidity is less than 90% (no condensation)
Size	Standard 32*32 positioning hole, compatible with 38*38 hole
Accessories	AHD Camera Manual, warranty card/certification, 1 dryer