



## SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: [cctv@ideacamera.com](mailto:cctv@ideacamera.com)

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

**4MP IR Waterproof Bullet AHD Camera with 4.0Megapixels 3.6mm Fixed Lens, AHD/CVI/TVI/CVBS 4-in-1, UTC Control or OSD Menu optional.**



**Model Number: RC-BF60NAHD-4MPK**

**Key specifications:**

Image sensor: 4MP OV4689+ Full Han 8538M DSP

Effective pixels: 2592(H) x1520(V)

Lens: 4.0megapixels 3.6mm Fixed Lens (6,8mm optional).

Day and night: automatic (ICR)

Backlight compensation: automatic

Gain control: automatic

White balance: automatic

Infrared: 36pcs IR LEDs

IR distance: 30meters

IR-cut: supported

Night vision: supported

Infrared spectrum: 850nm

Waterproof casing: IP66

Casing Color: White

OSD MENU: Support multiple countries Languages (can switch)

**Production Advantages:**

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.



## SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: [cctv@ideacamera.com](mailto:cctv@ideacamera.com)

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Work with almost HD 5-in-1 Hybrid DVRs.

Lower price.

6-8 working day per order.

### Production applications:

This is the best product of safety field. It and hard disk video recorders、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.

Descriptions	4MP HD Analog Video Camera Module
Sensor	4MP OV4689_ Full han 8538M DSP
Video Resolution	PAL/NTSC : 2592*1520
Minimum Illumination	color: 0. 01Lux@ (F1.2, AGC ON) , 0Lux with IR
	Black & White: 0.001Lux@ (F1.2, AGC ON) , 0Lux with IR
Photosensitive Resistance	1 photosensitive resistance interface, support the photosensitive resistor input signal and image, IR-CUT,
Shutter	1/50(1/60) seconds to 1/100,000 seconds
Day and Night Function	Support IR-CUT
Lens Parameters	C/CS interface, M12 lens optional
Synchronous Mode	inter-sync
Noise-signal Ratio	>58dB
Temperature and Humidity	- 10 ℃~ 60 ℃, humidity is less than 90% (no condensation)
Power	DC12V±10%
Consumption	<5W
Size	Standard 38*38 positioning hole8