



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

2MP H.264 Indoor IR Smart WIFI Camera, Lightning connection, CAM365 Mobile App, Two-way intercom, Support TF Card (Max 64G), Motion detection.



FOB: US\$19.8/Per

Model: RC-WPTH-2MP

Product features:

Lightning connection, one key connecting the WIFI;

Easy installation and use, plug and play;

View the video anytime and anywhere, support multiple platforms, terminals, networks;

Clear and smooth video, intelligent transmission;

Bank level security control and ensure privacy;

Online firmware upgrade, update function and experience synchronously;

H.264 video compression, transmit HD video in narrow bandwidth. High picture quality, low bit stream, local HD video recording. Watch more smoothly and no streaking;

Support two-way audio, telecommunication level of signal processing, (echo cancellation, noise suppression, comfort noise, silence suppression);

Support Android /IOS system mobile devices, remote real-time monitoring;

Motion detection, linkage snapshot/video recording;

Real-time App push notifications;

Infrared night vision lighting (IR distance: 10 meters), 24 hours day and night monitoring, IR-CUT switch;

Support micro SD card (max 64 GB) storage;

Support QR code login;

Support detail zoom;

Support 2.4G WIFI (IEEE802.11b/g/n);

Support P/T/Z remotely (Horizontal: 350° & Vertical: 100°).



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Product specifications:

Display resolution	1920*1080 (2MP)
Lens	f: 3.6mm
Visual angle	H:80°; V:45°; D:92°
Sensor	H1668(Korean)CMOS
ISP	VS3030(American)
Minimum	0.01Lux
Input/output	Built-in microphone and speaker
Audio compression	AAC
Video compression	H.264
Lighting frequency	50Hz, 60Hz
Image frame rate	Max 30fps
Image resolution	2MP
Image adjustment	Brightness, Contrast, Saturation, Sharpness
White balance, BLC	Automatically
Night vision	6 infrared LED, IR distance: 10meters
Wireless networks	2.4G WIFI(IEEE802.11b/g/n),Built in PCB board 2DB antenna
Ethernet	10/100Mbps
Protocols	TCP/IP, UDP/IP, HTTP, DHCP, RTMP, MUTP
IP address	Static IP address and dynamic IP address
Support connecting RF	No
Face detection	No
POE	No
Pan & Tilt	Horizontal:350°& Vertical:100°
Alarm detection	Motion detection
Alarm linkage	Snapshot, audio/video record
Alarm notification	Real-time App push notifications
RF Peripheral	No
Power	DC 5V / 2A(Europe, UK, USA type for option) power
Buttons	A reset hole
Network interface	RJ45
Adjustable lens	No
Video storage	Micro SD(Max 64GB)
Work temperature	-10° ~ 55°C (14°F ~ 131°F)
Work humidity	10% ~ 80% (No condensation)
Storage temperature	-10°C ~ 60° (14°F ~ 140°F)
Storage humidity	0% ~ 90%(No condensation)



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Color	White and black
Certificate	ROHS, CE,FCC,NCC