



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

8CH 2SATA H.265 HD Professional NVR with 1ch Face Detection, Max 8ch Playback, Support Max 8CH 6MP IPC, ONVIF2.6, Support Cloud storage, VSS Mobile App.



Model: NVR-3208-JS

Key features:

- Video Output: 1* HDMI, 1* VGA.
- 2*USB 2.0 interface, 1* RS485 Interface.
- High performance chip (Hi3536).
- 1CH Face Detection or 2CH Perimeter Detection, smart research.
- H.265/H.264 Profile, Max 8ch 6MP IPC.
- Real-time Synchronous playback (Max 8ch).
- Bandwidth input: 64Mbps
- Support 8ch alarm in, 4ch alarm out.
- Support ONVIF 2.6, Digital zoom, 3G Dongle supported.
- Cloud storage (google drive/drop box), mobile alarm push.
- Support Two-way voice intercom, UPNP, mobile phone surveillance.
- Support Multi-Protocols, P2P, and Built-in free DDNS.
- Support mobile APP (VSS Mobile).
- Support computer client (IMS300).
- Support 2*10TB HDD
- With strong power (DV 12V 3.3A).

Offer services:

Offer 2-years product warranties.



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Logistics convenient.
OEM/ODM.
CCC/CE/FCC Certified.
Strict product quality control.
Lower price.
6-8 working day per order.

Applications:

This is the best product of safety field. It and CCTV camera、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.

Parameters:

Model		NVR-3208-JS	NVR-3216-JS	NVR-3224-JS
OS		Embedded Linux		
Video&Audio input	Incoming bandwidth	64Mbps	96Mbps	96Mbps
	Outgoing bandwidth	40Mbps	40Mbps	40Mbps
	IPC Input	8CH	16CH	24CH
	Audio In	1CH, RCA(Line out, 2Vp-p, 300ohms)		
Video&Audio output	CVBS	1CH, BNC(1.0Vp-p, 75ohms)		
	VGA	1CH, 1920×1080, 1280×1024, 1280×720, 1024×768		
	HDMI	Standard 1.4a		1920×1080, 1280×1024, 1280×720, 1024×768
		3840×2160, 1920×1080, 1280×1024, 1280×720, 1024×768		
	Audio Output	1CH, RCA(Line out, 2Vpp, 300ohms)		
Video&Audio encoding	Audio Compression	G. 711A		
	Audio Bit Rate	8Kbps(16bit)		
Video&Audio decoding	IP channel Resolution	Main stream: Up to 3264x2448 Auxiliary stream:D1		
	Video decoding	H. 265 (Main Profile@Level5.0) / H. 264(High Profile@Level5.1)		
	Audio decoding	G. 711A, G711U, G726		
	Synchronous Playback	Up to 8CH	Up to 16CH	
	Decoding Ability	8CH 720P@30FPS or 4CH 1080P@30FPS		
Intelligent Analysis		1CH Face detection or 1CH Perimeter detection	N/A	
		Up to 1080P		
Other Function	Bidirectional Talk	Two-way voice intercom function		
	Motion Detection	Zones: 396(22*18),Sensitivity: 1~6 (level 6 is highest)		
	Picture Capture	Support JPEG Capture		
HDD Interface	SATA	2 SATA Interfaces		
	Max Capacity	Unlimited		
External Interface	Network Interface	1 RJ45 10M/100M/1000M self-adaptive Ethernet interface		



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

	USB Interface	2 USB2.0 Interfaces		
	Alarm In	8CH		
	Alarm Out	4CH		
		NO/NC		
	RS-485	1 RS-485 interface		
Structure	Dimensions	405x335x120mm		
	Front Panel	JS		
	Size	1U, 360x262x48mm		
	Weight	2.3Kg (Without HDD)	2.3Kg (Without HDD)	2.3Kg (Without HDD)
	Installation	Desktop Installation		
General	Power Supply	DC +12V 3.3A	DC +12V 3.3A	DC +12V 3.3A
	Working Temperature	-10℃--+55℃		
	Working Humidity	10%--90%		
	Consumption	6W (without HDD, without POE)		