SHENZHEN RISE ELECTRONIC CO., LTD.
Website: http://www.ideacamera.com Email:cctv@ideacamera.com
Global Sources Homepage Address: http://www.globalsources.com/ideacamera.co

24CH 2SATA H.265 HD Professional NVR, Max 16ch Playback, Support Max 24CH 6MP IPC, ONVIF 2.6, Support Cloud Storage, Remote Control, VSS Mobile App.



Model: NVR-3224-JS

Key features:

Video Output: 1* HDMI, 1* VGA.
2*USB 2.0 interface, 1* RS485 Interface.
High performance chip (Hi3536).
H.265/H.264 Profile, Max 24ch 6MP IPC.
Real-time Synchronous playback (Max 16ch).
Bandwidth input: 96Mbps
Support 8ch alarm in, 4ch alarm out.
Support ONVIF 2.6, Digital zoom, 3G Dongle supported.
Cloud storage (google drive/drop box), mobile alarm push.
Support Two-way voice intercom, UPNP, mobile phone surveillance.
Support Multi-Protocols, P2P, and Built-in free DDNS.
Support mobile APP (VSS Mobile).
Support computer client (IMS300).
Support 2*10TB HDD
With strong power (DV 12V 3.3A).

Offer services:

Offer 2-years product warranties.
Logistics convenient.
OEM/ODM.

CCC/CE/FCC Certified.
Strict product quality control.
Lower price.
6-8 working day per order.

Applications:

This is the best product of safety field. It and CCTV camera、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.

Parameters:

Model		NVR-3208-JS	NVR-3216-JS	NVR-3224-JS
OS		Embedded Linux		
Video&Audio input	Incoming bandwidth	64Mbps	96Mbps	96Mbps
	Outgoing bandwidth	40Mbps	40Mbps	40Mbps
	IPC Input	8CH	16CH	24CH
	Audio In	1CH, RCA(Line out, 2Vp-p, 300ohms)		
Video&Audio output	CVBS	1CH, BNC(1.0Vp-p, 75ohms)		
	VGA	1CH, 1920×1080, 1280×1024, 1280×720, 1024×768		
	HDMI	Standard 1.4a		
		3840×2160, 1920×1080, 1280×1024, 1280×720, 1024×768		1920×1080, 1280×1024, 1280×720, 1024×768
	Audio Output	1CH, RCA(Line out, 2Vpp, 300ohms)		
Video&Audio encoding	Audio Compression	G.711A		
	Audio Bit Rate	8Kbps(16bit)		
Video&Audio decoding	IP channel Resolution	Main stream: Up to 3264x2448 Auxiliary stream:D1		
	Video decoding	H.265 (Main Profile@Level5.0) / H.264(High Profile@Level5.1)		
	Audio decoding	G.711A, G711U, G726		
	Synchronous Playback	Up to 8CH	Up to 16CH	
	Decoding Ability	8CH 720P@30FPS or 4CH 1080P@30FPS		
Intelligent Analysis		1CH Face detection or 1CH Perimeter detection	N/A	
		Up to 1080P		
Other Function	Bidirectional Talk	Two-way voice intercom function		
	Motion Detection	Zones: 396(22*18), Sensitivity: 1~6 (level 6 is highest)		
	Picture Capture	Support JPEG Capture		
HDD Interface	SATA	2 SATA Interfaces		
	Max Capacity	Unlimited		
External Interface	Network Interface	1 RJ45 10M/100M/1000M self-adaptive Ethernet interface		
	USB Interface	2 USB2.0 Interfaces		
	Alarm In	8CH		

	Alarm Out	4CH		
		NO/NC		
	RS-485	1 RS-485 interface		
Structure	Dimensions	405x335x120mm		
	Front Panel	JS		
	Size	1U, 360x262x48mm		
	Weight	2.3Kg (Without HDD)	2.3Kg (Without HDD)	2.3Kg (Without HDD)
	Installation	Desktop Installation		
General	Power Supply	DC +12V 3.3A	DC +12V 3.3A	DC +12V 3.3A
	Working Temperature	-10℃--+55℃		
	Working Humidity	10%--90%		
	Consumption	6W (without HDD, without POE)		