



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

64CH 8SATA H.264 HD Professional NVR, Support 16ch Realtime Playback, Support Face Detection, Support 64ch 6MP IPC Output, Support 4K video output, VSS Mobile App.



Model: NVR-8664-CU

Key Features:

High performance chip (Hi-3536);

64CH Face Detection work with VSS IP Camera (HISI);

Max support 64ch 6MP IP Camera;

Support 4K video output;

H.264 / H.265 Format, ONVIF 2.6;

IP input: 64ch@720/960/1080P / 3.0/4.0MP/5.0MP/6.0MP@30fps;

Bandwidth: 256Mbps

8SATA*10TB, 1 x E-SATA, (DVD RW optional), Max 1~16ch real-time playback;

2 x VGA ports, 2 x HDMI output, Audio: 64ch in by RJ45, 1ch in by RCA, 1ch out by RCA;

Support Multi-Protocols, P2P, Cloud Storage;

Built-in free DDNS, UPNP, 3G Dongle supported, Digital zoom, Mobile phone surveillance;

2 x RJ45, 2 x HDMI, 2 USB2.0, remote, mouse;

Mobile APP Name: VSS Mobile

Power In (AC 110~240V);

Offer services:

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Lower price.

6-8 working day per order.

Applications:

This is the best product of safety field. It and CCTV camera、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community、or a large public places, etc.

Parameters:

Model	NVR8632-CU	NVR8664-CU	NVR86128-CU
OS	Embedded Linux		
Video&Audio input	Bidirectional Talk 1CH, RCA (Line in,2Vp-p,1Kohms)		
	Incoming bandwidth	200Mbps	256Mbps



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

	IPC Input	32CH	64CH	128CH
Video&Audio output	VGA	1CH,1920×1080,1280×1024,1280×720,1024×768		
	HDMI	Standard 1.4		
		3840×2160,1920×1080,1280×1024,1280×720,1024×768		
	Audio Output	1CH, RCA (Line out,2Vp-p,300ohms)		
Video&Audio encoding	Audio Compression	G.711A		
	Audio Bit Rate	64Kbps		
Video&Audio decoding	IP channel Resolution	Main stream: Up to 3264x2448 Auxiliary stream: D1		
	Video decoding	MPEG-4/H.264(Up to High Profile@Level5.0)		
	Audio decoding	G.711A/G.726		
	Synchronous Playback	Up to 16CH	Up to 16CH	Up to 16CH
	Decoding Ability	16CH 1080P@30FPS		
Other Function	Bidirectional Talk	Two-way voice intercom function		
	Motion Detection	Zones: 396(22*18), Sensitivity: 1~6 (level 6 is highest)		
	Picture Capture	Support JPEG Capture		
HDD Interface	SATA	8 SATA Interfaces		
	eSATA	1 eSATA Interface		
	Max Capacity	Unlimited		
External Interface	Network Interface	2 RJ45 10M/100M/1000M self-adaptive Ethernet interfaces		
	USB	3 USB2.0 Interfaces		
	Alarm Input	16CH		
		Open/Closed Relay		
	Alarm Output	4CH		
		NO/NC		
	RS-232	1 RS-232 interface		
	RS-485	1 RS-485 interface		
Structure	Dimensions	520*520*215mm		
	Size	2U,441*448*88mm		
	Weight	7Kg (without HDD)		
	Installation	Rack installation, Desktop installation		
General	Power Supply	110V~220V±10%, 47Hz~63Hz		
	Working Temperature	-10°C-- +55°C		
	Working Humidity	10%--90%		
	Consumption	30W (without HDD)		