



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

8CH 1080P H.265 HD NVR, Max 8ch Playback, 8pcs POE ports, VSS Mobile App.



Model: NVR-2208L-P8/JN

Key features:

- Video Output: 1* HDMI, 1* VGA
- 2*USB 2.0 interface
- 1*RS485 Interface
- 8*POE Ports

Key functions:

- High performance chip (Hi3536D).
- IPC (8CH 720P@20FPS or 4CH 1080P@20FPS).
- H.265/H.264 Profile.
- Real time Playback (Max 8ch).
- Bandwidth input: 32Mbps
- Support ONVIF 2.6, Digital zoom, 3G Dongle supported.
- Cloud storage (google drive/drop box), mobile alarm push.
- Support Two-way voice intercom, UPNP, mobile phone surveillance.
- Support Multi-Protocols, P2P, and Built-in free DDNS.
- Mobile APP Name (VSS Mobile).
- Support computer client (IMS300).
- Support 1*10TB HDD
- With strong power (DC 48V 1.875A).

Offer services:

- Offer 2-years product warranties.
- Logistics convenient.
- OEM/ODM.
- CCC/CE/FCC Certified.
- Strict product quality control.
- Lower price.



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

6-8 working day per order.

Applications:

This is the best product of safety field. It and CCTV camera、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community、or a large public places, etc.

Parameters:

Model		NVR-2204L-P4/JN	NVR-2208L-P8/JN
OS		Embedded Linux	
Video&Audio input	Incoming bandwidth	32Mbps	32Mbps
	IPC Input	4CH	8CH
Video&Audio output	VGA	1CH,1920×1080,1280×1024,1280×720,1024×768	
	HDMI	1.4b 1920×1080,1280×1024,1280×720,1024×768	
Video&Audio decoding	IP channel Resolution	Main stream: Up to 2560x1440 Auxiliary stream: D1	
	Video decoding	H.265 (Main Profile@Level 4.1) /H.264(Up to High Profile@Level 4.2)	
	Audio decoding	G.711A/G711U	
	Synchronous Playback	4CH	8CH
	Decoding Ability	4CH 1080P@20FPS	8CH 720P@20FPS or 4CH 1080P@20FPS
Motion Detection	Motion Detection	Zones: 396(22*18), Sensitivity: 1~6 (level 6 is highest)	
	Picture Capture	Support JPEG Capture	
HDD Interface	SATA	1 SATA Interface	
	Max Capacity	Unlimited	
POE Interface	POE Interface	4CH	8CH
		IEEE 802.3af	IEEE 802.3af
		RJ-45 10/100 Mbps self-adaptive Ethernet interface	RJ-45 10/100 Mbps self-adaptive Ethernet interface
	Power	≤45W	≤45W
External Interface	Network Interface	1 RJ45 10M/100M self-adaptive Ethernet interface	
	USB	2*USB2.0	
Structure	Dimensions	410*293*60mm	
	Size	215*235*45mm	
	Weight	1.7KG	
	Installation	Desktop Installation	
General	Power Supply	DC 48V 1.35A	DC 48V 1.875A
	Working Temperature	-10°C-- +55°C	-10°C-- +55°C
	Working Humidity	10%--90%	10%--90%
	Consumption	7W (without HDD)	7W (without HDD)